

 SHARE

Excavators / E20 Compact Excavator

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Units US

Bobcat E20

Engine

Emissions Tier (EPA)	Tier 4
Engine Fuel	Diesel
Maximum Governed RPM	2,500 rpm
Horsepower	13.9 hp
Turbocharged Engine	N/A
Optional Horsepower	n/a

Performance

Operating Weight	4,306 lb
Weight Class	2 t
Travel Speed - High	2.5 mph
Travel Speed - Low	1.5 mph
Arm Digging Force	2,086 lbf
Bucket Digging Force	4,684 lbf
Rated Lift Capacity	1023 lb
Lift Radius	118 in
Boom Swing - Left	80°
Boom Swing - Right	60°
Maximum Dig Depth	8.5 ft
Max Dump Height	8.8 ft
Maximum Reach at Ground Level	14 ft

Capacities

Fuel Tank	5 gal
-----------	-------

Hydraulic System

Auxiliary Std Flow	7.9 gal/min
Auxiliary Pressure	2,610 psi

Dimension

Length	145.2 in
Overall Length in Travel Position	145.2 in
Width	39 in
Height	90.4 in
Height with Operator Cab	90.4 in

Features

Air Conditioning	N/A
Cab Enclosure	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Heater Air Conditioning	N/A
Radio	<input checked="" type="checkbox"/>
Tail Swing Type	Zero
Engine Shutdown	<input type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Secondary Auxiliary Hydraulics	N/A
Quick Tach System	N/A
Rubber Track	<input type="checkbox"/>
Selectable Auxiliary Hydraulic Flow	<input checked="" type="checkbox"/>
Angle Blade	N/A

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.